

Tamaño / Size				Peso Nominal / Nominal Weight				Presión de Prueba (psi) / Test Pressure (psi)		Tipo de Roscado / Type of Thread		
Diámetro Ext. / Outside Diameter		Espesor / Wall Thickness		Extremo Liso / Plain ends		Roscado y Cople / Threads and Couplings		H-40	J-55&K-55	Corto / Short	Largo / Long	But-ress
in	mm	in	mm	lb/ft	kg/m	lb/ft	kg/m	Std.	Std.			
4 1/2	114.3	0.205	5.21	9.40	13.99	9.50	14.14	2900	4000	X	---	---
		0.224	5.69	10.23	15.22	10.50	15.63	-----	4400	X	---	X
		0.250	6.35	11.35	16.89	11.60	17.26	-----	4900	X	X	X
5*	127	0.220	5.59	11.24	16.74	11.50	17.11	-----	3900	X	---	---
		0.253	6.43	12.84	19.12	13.00	19.35	-----	4500	X	X	X
		0.296	7.52	14.88	22.16	15.00	22.32	-----	5200	X	X	X
5 1/2*	139.7	0.244	6.2	13.71	20.41	14.00	20.83	2800	3900	X	---	---
		0.275	6.9	15.36	22.85	15.50	23.07	-----	4400	X	X	X
		0.304	7.72	16.89	25.13	17.00	25.30	-----	4900	X	X	X
6 5/8	168.3	0.288	7.32	19.49	29.01	20.00	29.76	2800	---	X	---	---
		0.288	7.32	19.49	29.01	20.00	29.76	-----	3800	X	X	X
7*	177.8	0.231	5.87	16.72	24.89	17.00	25.3	2100	-----	X	---	---
		0.272	6.91	19.56	29.12	20.00	29.76	2500	3400	X	---	---
		0.317	8.05	22.65	33.70	23.00	34.23	-----	4000	X	X	X
7 5/8*	193.6	0.300	7.62	23.49	34.96	24.00	35.72	2500	-----	X	---	---
		0.328	8.33	25.59	38.08	26.40	39.29	-----	3800	X	X	X
8 5/8	219.1	0.264	6.71	23.57	35.08	24.00	35.72	-----	2700	X	---	---
		0.304	7.72	27.02	40.21	28.00	41.67	2300	---	X	---	---
9 5/8*	244.5	0.312	7.92	31.06	46.20	32.30	48.07	2100	---	X	---	---